

MF Freezer Specification Chart

Description	Specification per Cylinder			
	MF-400	MF-600	MF-800	MF-1500
Pump drive - kW/HP	0.75/1	0.75/1	1.1/1.5	1.1/2
Mix inlet and ice cream outlet connection to CP pump	1.5/38	1.5/38	1.5/38	1.5/30
Dasher drive kW/HP	1.5/38	7.5/10	11/15	18.5/25
MIX CAPACITY:				
Minimum - maximum - US gallons per hour	20-105	13-80	20-105	75-750
Minimum - maximum - liters per hour	40-200	50-300	80-400	75-750
ICE CREAM CAPACITY @ 100% OVERRUN:				
Minimum - maximum - US gallons per hour	20-105	26-158	42-210	40-400
Minimum - maximum - liters per hour	80-400	100-600	160-800	150-1500
AIR REQUIREMENTS:				
nl/hour	300	400	500	850
Connections mm	ø8	ø8	ø8	ø8
AIR PRESSURE REGULATOR AND SANITARY FILTER ARE FACTORY SUPPLIED				
MAIN POWER REQUIREMENTS: Phase x voltage, cycles	3 x 400, 50 Hz	3 x 400, 50 Hz	3 x 400, 50 Hz	3 x 400, 50 Hz
MINIMUM CLEARANCES AROUND FREEZER FOR SERVICING:				
Front (or according to local regulations) - inch/mm	30/750	43 (1100)	47/1190	44/1220
Sides - inch (mm)	17.7 (450)	17.7 (450)	17.7 (450)	18/460
Rear - (inch)	30 (760)	30 (760)	30 (760)	30 (760)

To obtain product literature or further details on model dimensions, variations and availability contact:

Ice Cream & Process Solutions (Pty) Ltd.

Phone: **(07) 3272 2153**

Fax: **(07) 3272 2581**